


FICHA TECNICA ACELERADOR ZMB

Accelerator



Zinc Dimethyldithiocarbamate

Form:	White powder and Naugets.
Specific Gravity:	1.68
Melting Range:	240-250°C (464-482°F)
Solubility:	Slightly soluble in water and organic solvents.
Storage Stability:	In excess of four (4) years when stored under normal conditions in a cool dry place away from any direct sources of heat and light.
Handling Precautions:	Moderately toxic. Contact with eyes or skin can cause irritation. Exposure to this material when alcohol is consumed can produce an adverse reaction. Observe good personal hygiene.
Features:	A very fast curing accelerator with a low activation temperature. The processing safety can be increased by combining with MBTS.
Discoloration:	Nonstaining and nondiscoloring.
Recommended Uses:	Used in wire insulation and jackets, dipped goods, latex compounds, cements, footwear and molded goods.
FDA Status:	175.105 — Adhesives — <i>No Limitations</i> 177.2600 — Rubber Articles Intended for Repeated Use — <i>Limitation — 1.5% Max.</i> 178.3100 — Animal Glue — <i>No Limitations</i>

Oficina

Av. Neptuno No.33
Col. Arcos de la Hacienda. Cuautitlán Izcalli, EdoMex. C.P. 54730
Telefonos: 52+ 555896-4534 / 555889-4446 / 555889-4422

www.ameripolchemical.com

E-mail: direccion@ameripolchemical.com.mx

almacen y planta

A.V uno norte No.15
Bodega 1C Parque industrial Cartagena
Tultitlan Edo. De Mexico
C.P. 54934 Tel. 58882286

